

PATENT ABSTRACTS OF JAPAN

(11)Publication number:

64-079919

(43) Date of publication of application: 24.03.1989

(51)Int.CI.

G11B 5/66

G11B 5/704 G11B 5/706

G11B 5/82

(21)Application number : 62-238213

(71)Applicant: HITACHI MAXELL LTD

(22)Date of filing:

22.09.1987

(72)Inventor: KUBOTA TAKASHI

YANO AKIRA WAKAI KUNIO

OSHIMA KIYOTAKA

(54) MAGNETIC DISK AND ITS PRODUCTION

(57) Abstract:

PURPOSE: To improve magnetic characteristics by laminating a ferromagnetic layer consisting of a prescribed metal on an underlying layer consisting of a prescribed metal and diffusing and segregating the underlying metal into the <u>ferromagnetic layer</u>.

CONSTITUTION: The underlying layer consisting of the metal selected from Cr, Cu, Mn, Mo, Si, Ta, Ti, V, and W or the alloy thereof is formed on a nonmagnetic substrate. The ferromagnetic layer consisting of Co or essentially consisting of Co is laminated thereon. After this substrate is heated to the crystal phase transformation point (W400°C) of the material forming the ferromagnetic material or above, the substrate is cooled under impression of a magnetic field in the horizontal direction (circumferential direction of a disk) to diffuse and segregate the underlying metal into the magnetic layer. The substrate is preferably subjected to a previous heating treatment at ≥700°C in this case. A glass or ceramic substrate is used for the substrate.

LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

translation ordered 5/17/12



[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2000 Japan Patent Office